

Модель	Усилие (кН)	Макс. длина гиба (мм)	Расстояние между стойками (мм)	Зев (мм)	Ход (мм)	Раскрытие (мм)	Мощность двигателя (кВт)	Объем масла (л)	Скорости (мм/с)			Габариты (мм)			Масса (кг)
									Скорость подвода	Рабочая скорость	Скорость отвода	Длина	Ширина	Высота	
TSM-50/1650	500	1650	1200	300	160	470	5.5	200	220	0-15	180	2180	1340	2385	4300
TSM-60/2050	600	2050	1500	300	160	470	7.9	200	220	0-15	180	2680	1340	2385	4600
TSM-80/2500	800	2500	2000	300	225	425	7.9	200	200	0-15	180	2800	1470	2410	6100
TSM-110/2500	1100	2500	2000	400	225	500	10.5	200	220	0-15	180	3010	1670	2720	7800
TSM-110/3100	1100	3100	2700	400	225	500	10.5	200	220	0-15	180	3710	1670	2720	9000
TSM-110/4100	1100	4100	3600	500	225	500	10.5	200	220	0-15	180	4610	1770	2720	10900
TSM-130/2500	1300	2500	2000	400	225	500	10.5	200	200	0-15	160	3010	1670	2720	7800
TSM-130/3100	1300	3100	2700	400	225	500	10.5	200	200	0-15	160	3710	1670	2720	9000
TSM-130/4100	1300	4100	3600	500	225	500	10.5	200	200	0-15	160	4610	1770	2720	11300
TSM-130/5100	1300	5100	4600	400	225	500	15.7	200	180	0-15	130	5610	1820	2960	15200
TSM-130/6100	1300	6100	5600	400	225	500	15.7	200	180	0-15	130	6610	1820	3110	17700
TSM-160/3100	1600	3100	2700	450	200	475	15.7	200	200	0-15	160	3500	1700	2720	9800
TSM-160/4100	1600	4100	3600	450	200	475	15.7	200	200	0-15	160	4500	1700	2720	11500
TSM-170/2500	1700	2500	2000	400	225	500	15.7	200	200	0-15	160	3030	1680	2720	8700
TSM-170/3100	1700	3100	2700	400	225	500	15.7	200	200	0-15	160	3730	1680	2720	10100
TSM-170/4100	1700	4100	3600	500	225	500	15.7	200	200	0-15	160	4630	1790	2720	12100
TSM-170/5100	1700	5100	4600	400	225	500	15.7	200	160	0-15	110	5630	1800	2960	17000
TSM-170/6100	1700	6100	5600	400	225	500	15.7	200	160	0-15	110	6630	1800	3160	20000
TSM-210/2500	2100	2500	2000	400	225	500	15.7	200	160	0-13	150	3030	1680	2720	9000
TSM-210/3100	2100	3100	2700	400	225	500	15.7	200	160	0-13	150	3730	1680	2720	10500
TSM-210/4100	2100	4100	3600	500	225	500	15.7	200	160	0-13	150	4630	1790	2720	13100
TSM-210/5100	2100	5100	4600	400	225	500	15.7	200	130	0-13	110	5630	1850	3100	18000
TSM-210/6100	2100	6100	5600	400	225	500	15.7	200	130	0-13	110	6630	1850	3210	21000
TSM-250/2500	2500	2500	2000	400	250	525	19.3	460	130	0-13	130	3050	1920	2975	11700
TSM-250/3100	2500	3100	2700	400	250	525	19.3	460	130	0-13	130	3750	1920	2975	14000

TSM-250/4100	2500	4100	3600	400	250	525	19.3	460	130	0-13	130	4650	1920	2975	16000
TSM-250/5100	2500	5100	4600	400	250	525	19.3	460	120	0-13	110	5650	1920	3125	21200
TSM-250/6100	2500	6100	5600	400	250	525	19.3	460	120	0-13	110	6650	1920	3325	24600
TSM-320/3100	3200	3100	2700	400	300	575	24.1	460	100	0-13	110	3930	2110	3205	17700
TSM-320/4100	3200	4100	3600	400	300	575	24.1	460	100	0-13	110	4830	2110	3205	20300
TSM-320/5100	3200	5100	4600	400	300	575	24.1	460	90	0-13	90	5830	2150	3690	26100
TSM-320/6100	3200	6100	5600	400	300	575	24.1	460	90	0-13	90	6830	2150	3855	30400